



FOREST FIRE DETECTION AND MONITORING THROUGH ACOUSTIC SIGNAL PROCESSING WITH DEEP LEARNING

¹Maneesha.C.M, ²Ms.Divya.P

¹MCA Scholar, ²Assistant Professor

¹Department of MCA

Abstract: Forests are one of the most important ecosystems on Earth. They play a vital part in regulating the climate and act as a renewable source of air for mortal beings. still, timbers are really floated by fires. When backfires do outside of their natural range or size, they can come a real pitfall to life and property. In this paper, we propose an original new approach for detecting timber backfires, rested on collected data of fire sounds. This system employs a deep knowledge (DL) model to anatomize and classify terrain sounds into two classes “Fire” or “No fire” (usual timber sounds). The model must first be trained on a set of environmental sounds in order to learn and descry fire sound patterns from other sounds. With this model, we achieve an emotional delicacy of 94.24 on the testing sub- dataset. especially, the model consists of only parameters, rendering it exceptionally feathery. This quality makes it largely conducive for deployment across various platforms analogous as IoT bias, bedded systems, or mobile bias. Integrating this model into timber surroundings and fortifying it with complementary tools for comprehensive validation could enable us to directly notify decision- makers or applicable authorities, easing timely and decisive conduct.

Index Terms - Audio environment, Backfires, Deep Learning (DL), Forest Fire Sound spectrum, Wildfires.

I.INTRODUCTION

One of the most significant ecosystems is the forest, which makes up nearly one-third of the planet's land area. They are home to numerous endangered species as well as more than two-thirds of the terrestrial biodiversity. Carbon sequestration, soil erosion prevention, water purification, and climate change mitigation are just a few of the vital ecological services that forests offer [1]. They're also crucial rudiments to the livelihoods of millions of people around the world, furnishing wood for energy and construction, food, and traditional drug. But timbers are vulnerable to catastrophes similar as backfires. Backfires are a natural part of the timber life cycle. still, when they do in areas with a high position of mortal conditioning, they can beget great damage to both the natural terrain and mortal structure. In addition, backfires can spread snappily and be delicate to control, making them a serious trouble to life and property. Numerous factors can contribute to a campfire, similar as a failure, lightning, and careless mortal conditioning. In recent times, the number of backfires has been adding, due in part to climate change. As the world gets warmer, dry conditions come more common and compound the readiness of timbers to be fired. Backfires can have a ruinous impact on timbers. They can destroy trees, wildlife territories, and climaxes. They can also release adulterants into the air and beget respiratory problems for people. In some cases, backfires can indeed lead to the loss of mortal life [2]. While backfires can make great detriment, they also give some benefits to the timbers; they can help to control nonentity populations and promote the growth of new conditions. When backfires do in a natural setting, they can ameliorate the overall health of the timber. still, the negative impacts of backfires far outweigh the positive bones. That's why it is so important to take way to help them. Beforehand discovery of backfires is critical to containing these disasters. utmost countries use traditional styles for detecting fires including lookouts, ground details, and aircraft, others are enforcing the rearmost technologies, which enable us to develop new styles for detecting and monitoring timber fires in their foremost stages and spread. One common system is using upstanding discovery, with satellites, aircraft, or drones [3]. Another system is using ground- based IoT detectors, installed directly in a network inside a timber. These detectors can descry heat, bank, and other pointers of a fire [4]. Our donation in this paper lies in a new approach to descry timber backfires. This system involves exercising original sound data and potentially integrating fresh sensors, analogous as temperature, humidity, carbon monoxide detectors, and cameras. Employing deep knowledge models, we conduct automated analysis of fire- related audial signals, enabling the identification of distinctive patterns associated with fires. This information could be of great mileage to advise the applicable authorities to take suitable way.

II. LITERATURE REVIEW

Grari et al. [1] offer an integral analysis of the intersection between Internet of Things (IoT) technologies and machine learning (ML) in timber fire spotting and control. They explore different IoT- based systems co-opted with ML models, emphasizing their capabilities in early discovery, real- time monitoring, and prophetic analytics. The review emphasizes the eventuality of assimilating these technologies for productive timber fire mitigation while manipulating difficulties similar as data diversity and deployment in remote areas.

Yandouzi et al. [2] focus on the employment of deep learning and drone technology in detecting and forecasting timber fires. The study reviews preferences in deep learning models designed for image and video analysis collected via drones, featuring their precision in detecting fire patterns. The authors also explain the advantages of drone- grounded systems, including mobility, elasticity, and their capability to operate in dangerous surroundings, making them necessary for contemporary timber fire operation.

Kherraki and El Ouazzani's [7] work on deep convolutional neural networks (CNNs) for traffic monitoring offers perceptivity into CNN infrastructures that can be acclimated for campfire discovery. Their emphasis on real- time bracket aligns with the conditions of time-sensitive forest fire covering systems.

III. BACKGROUNDS

3.1 Data and Sources of Data

Detectors are bias that measure or descry a physical or chemical property and also convert it into a signal that can be read by a bystander or a recording device. There are all feathers of different detectors out there that measure all feathers of different effects [1]. Temperatures, pressure, light, sound, electricity, and captivation are just a many of the numerous effects that detectors can measure. They're also used in scientific exploration, artificial processes, and manufacturing [5].

One of the most common types of detectors that play an important part in detecting and fighting backfires are:

- The temperature detector, come by all shapes and sizes but they all serve the same purpose to measure the temperature of commodity. Temperature detectors are one of the most important types of detectors for detecting backfires. By measuring the temperature of the air, these detectors can give an early warning of a implicit fire.
- Moisture detectors are another important type of detector for detecting backfires. By measuring the moisture of the air, these detectors can help to identify areas at threat of backfires.
- Gaz detectors are another type of detector that can be used for detecting backfires. By measuring the position of gas in the air, these detectors can give an early warning of a implicit fire.
- Infrared detectors are also another type of detector that can be used for detecting backfires. These detectors can descry the heat hand of a fire, indeed if it isn't yet visible to the naked eye.
- Another detector is the Microphone; which is a transducer that converts sound into an electrical signal. The converted electrical signal can be used to perform colorful operations.

3.2 Sound

Sound is a form of energy that travels through the medium, or any other medium in the form of waves. These swells are created by climate, which beget patches in the medium to oscillate back and forth. Sound swells spread, when commodity vibrates; the frequence of the swell determines the pitch of the sound. It's the number of times per second a swell oscillates. Hertz (Hz) is the unit used for quantifying the frequence. The mortal observance can descry sound swells with frequence ranging from 20Hz to 20 kHz. The loudness of a sound swell is determined by its breadth; the more pressure swells present, the louder is the sound. The mortal observance can descry sounds with confines as low as one trillionth of an atmospheric pressure change. The sound's speed is dependent on the medium in which it travels. Sound swells trip the fastest through solids, also liquids, and eventually feasts; the speed of sound in air is roughly 343 m/s [6]. Fire sounds are one of the most recognizable and distinctive signals in the world. When it comes to fire, the sound of fire is unmistakable. whether it is a small bonfire or a raging timber fire; the sound as the air is dragged into the fire. The combination of these two sounds (creaking and whooshing) creates a distinctive sound frequently associated with fires. When combined with brume produced by the evaporation of humidity out from wood, the waste feasts from combustion enlarge due to the heat and must flee. The position of noise generated by fire depends on the humidity content of the burning wood, and the type of tree or backwoods. Dried wood with a high humidity content will crinkle and pop of the creaking dears, the hiss of embers, and the snapping of dears, as well as wood popping and exploding, is both soothing yet stirring. Burning wood and other backwoods produce a crackling sound as the fire consumes them. We also hear a wheezing sound as the air is dragged into the fire. The combination of these two sounds (creaking and whooshing) creates a distinctive sound frequently associated with fires. When combined with brume produced by the evaporation of humidity out from wood, the waste feasts from combustion enlarge due to the heat and must flee. The position of noise generated by fire depends on the humidity content of the burning wood, and the type of tree or backwoods. Dried wood with a high humidity content will crinkle and pop further. When heat expansion forces water vapor to get out from the wood by forming brume. Because of this, the fire erupts with popping and creaking sounds. As a result, when the wood has a high humidity content, the sound of popping and creaking can be heard more easily.

3.3 Deep Learning (DL)

Deep Literacy is a Machine Learning fashion that uses a deep neural network to learn from data. Deep literacy is used to break complex problems that are delicate to break using traditional machine literacy styles [7],[8]. Deep literacy is well suited for problems that are delicate to break using traditional styles, similar as image recognition and bracket, natural language processing, and machine restatement. Deep literacy is used in numerous operations similar as computer vision, natural language processing, and prophetic analytics [9].

Convolutional neural networks (CNNs) are one of the sorts of deep literacy neural networks that are generally used to dissect visual data [10]. CNN, like standard neural networks, consists of an input subcaste, an affair subcaste, and several retired layers in between, but on the other hand, are distinguished from normal neural networks by their capability to prize features from input images and use the spatial relationship between pixels in order to ameliorate pattern recognition.

CNN's have been applied to a number of operations, similar as picture bracket, object identification, and face recognition. CNN has attained state- of- the- art performance on a number of these tasks in recent times [11]. generally, CNNs are constructed using a race of convolutional layers followed by completely linked layers, convolutional layers excerpt information from the input images and further them to the posterior subcaste, and completely connected layers combine the convolutional layers' collected features and use them to produce prognostications (see Fig. 1) [12].




Fig.1: The Architecture of CNN Model

IV PROPOSED METHODOLOGY

Our new approach relies on using IoT detectors for detecting timber backfires. The focus is acquainted to sounds rather than observable dears. These new sound detectors will support other habituated classical detectors and will be stationed attached to trees in safe positions from both creatures and humans while gathering the most data in the air with the maximum content. It transmits this information over Lora protocol to the fog gateway, once these detectors have collected data on temperature, moisture, and CO. immaculately, the gateway at the fog knot should be deposited in a high position so that it can admit and transmit data from and to IoT bias without hindrance. It processes the collected data. When it comes to sound data, deep literacy will be applied to automatically fete patterns that may indicate the presence of an active fire in the timber. Using this information, authorities may be advised and take necessary conduct to put out the campfire. Data subsequently is delivered to pall waiters for fresh analysis, storehouse, and dashboarding exercising featherlight MQTT protocol via 2/ 3/ 4/ 5G, satellite internet, or any possible communication fashion available at the timber position.

We conduct our exploration trial in three phases dataset collecting, spectrogram production, and eventually, the construction of a sound deep learning model (see Fig. 2).




Fig.2: Research Experiment Phase

4.1 Sound Dataset Collection

Datasets of sounds can be collected in colorful ways, depending on the asked operation [8]. For illustration, a speech recognition system might be trained on a dataset of recorded speech samples, while a system for relating environmental sounds might be trained on a dataset of natural sounds like drops or birdcalls. In general, collecting a good dataset of sounds generally involves recording a variety of sounds in different surroundings and at different times [14]. We make this task with special- purpose sound recording outfit, or with a brace of regular microphones and a digital audio archivist. In our trials, the dataset used to train our models is derived from three sources Google Audio set (a vast collection of mortal- labeled ten seconds environmental sound patches attained from YouTube), A Kaggle Forest Wildfire Sound Dataset, and a set of sounds recorded with our smartphone microphone over a supervised tone- made fire with original tree wood. The collected sounds are divided into two orders the first one is named "Forest environment" it contains the major sounds that may be heard in a timber, coming from beasties, snorts, nonentity, Rain, Waterfall, Wind, Speech, Silence, Vehicles, and Aircraft; the alternate order includes only Fire sounds. What results, after drawing mixed and spoiled sounds, into 1044 samples in aggregate; 684 with the marker "timber terrain" which correspond to the " No Fire" affair of our DL model, and 360 with the marker "Fire". subsequently, we divided the dataset into training (60%), substantiation (20%), and testing (20%) sets, before any farther preprocessing or training. The breadth of the waveform is shown on the y- axis of a time series of these audio samples. It's standard practice to quantify breadth in terms of the change in pressure around the microphone or entering device that first detected the sound. In order to train our model, we used these time series signals as inputs. A visual analysis of the samples taken from each of the two classes in our dataset (Fire and terrain sounds) reveals that the waveform doesn't give egregious class identification information.

4.2 Spectrogram Generation

Proposed deep learning model is a neural network composed of a sequence of multiple layers

- The input level that resizes the input images to 64x64;
- The second level normalizes the images. It's generally used to ensure that the activations of the neurons in the network stay within a certain range, which makes training more stable and improves the conception performance of the model.
- The convolution 2d level convolves the images with 32 pollutants. A complication is an operation that takes two inputs, a sludge, and an input image, and produces an affair image. The affair image is produced by the complication operation, which is a matrix addition between the input image and the sludge [12].
- The batch normalization level batch- normalizes the convolved images. Batch normalization is generally used after the convolutional or completely connected layers, while level normalization can be used anywhere in the network. Both batch normalization and normalization layers have been shown to be veritably effective at perfecting the training and conception performance of deep neural networks.
- The dropout tier drops out an arbitrary 20% of the neurons. This subcaste is a regularization fashion for neural networks that helps help overfitting. The dropout subcaste aimlessly drops out (sets to zero) a number of affair units from the former layer during training. The dropout values are chosen aimlessly.
- The flatten tier that flattens the 32 adulterants into a vector. A flattened level takes an input with a potentially high-dimensionality and flattens it into a 1D tensor with shape (samples, smoothed dimension). This is useful for feeding thick layers since a thick position expects its input to be 1D [17].
- The three thick layers (completely connected layers) that have independently 1056, 264, 18 neurons.

The total number of parameters is 1789, which means that our proposed model is a feather light one (because it's fairly small and does not bear a lot of computational coffers compared to other deep learning models), and would be perfect for use in a resource- constrained terrain similar as IoT equipment , mobile equipment , or bedded systems. This model would be suitable to run snappily and efficiently while still furnishing good delicacy (see Fig.3).




Fig.3: Proposed Model Architecture

V. RESULTS AND DISCUSSION

5.1 Hardware and Software Characteristics

For our experimentation, we've used TensorFlow v 2.8.0, an open- source data analysis and machine literacy software library, on a high performance computing system (HPC) equipped with the following hardware specifications:

- Two Intel Gold 6148 (2.4 GHz/20 cores) processors.
- Two NVIDIA Tesla V100 graphics cards, each with 32GB of RAM.

5.2 Evaluation Matrix

We estimated our deep learning models using two criteria namely, Sparse Categorical Cross Entropy Loss, and Accuracy.

5.2.1. Sparse Categorical Cross Entropy Loss

Sparse categorical cross-entropy loss is a loss function used in machine and deep learning. This function is used when the markers aren't one-hot decoded. SCECE allows using integers as markers rather of one-hot encoding them. It's more effective than categorical cross-entropy loss and is generally used when the number of classes is large [18].

5.2.2 Accuracy

In predictive modeling, machine, and deep learning, the accuracy standard is used to assess the quality of prognostications. The accuracy standard is a measure of how accurate a model is in its forecasts. It's the proportion of accurate predictions to total prognostications. This metric could be used to compare different models and identify the most accurate one [20].

5.2.3 Evaluating the Results

We train our proposed model over 300 times to watch its gesture and attain the formal results. The model was inspired by Google's YAMNet, but with different tweaks due to overfitting on our dataset, particularly at batch normalization and global maximum pooling 2d layers. Timber fire discovery using sound detectors and deep learning is still in its early stages of development and therefore has limitations (the use of detectors in general for timber fire discovery has several limitations); detectors aren't suitable to determine all types of fires or smoldering fires (which produce little to no bank). Meanwhile, our system may be corroborated with other generally used detectors, similar as temperature, moisture, and smoke detectors, which can give supplementary data to increase the perfection of timber fire discovery. We may further degrade the rate of false positives by sending drones to the area around the suspicioned fire (the position can be acquired from the localization of the deployed detectors, similar as GPS or Galileo) to find out if a fire is started or not.

VI. CONCLUSIONS

In this study, we introduce a emerging approach that capitalizes on sound- to- image conversion and leverages the elevations in deep learning within computer vision. Our innovative system focuses on early timber fire discovery, shirking traditional dependence on visible flames in courtesy of demonstrating sound data. By employing deep learning, we automatically study fire- related audial signals, relating distinctive patterns reflective of a fire's presence, and instantly waking authorities for necessary conduct. specially, our proposed model achieves a well 94.24 accurateness on the test dataset while remaining hugely effective with a bare 1789 parameters, making it exceptionally capable for resource- constrained environs similar as IoT and mobile equipment. There are some boundaries to this study that will be handled in our coming works, the most eminent one is the small size of our applied dataset. This dataset contains only 1044 sounds, which is moderately lower than our target. Despite its limits, the outcomes of this study exhibit that the proposed model is a encouraging approach for the early finding of timber fires. As a perspective, we plan to fix our suggestion inside a forestland located in the surroundings of our university.

VII. CHALLENGES AND FUTURE WORKS

7.1 Challenges

Sound technology for forest fire detection faces significant hurdles, primarily environmental noise interference and signal attenuation. Forests are filled with ambient sounds from wind, rain, animals, and human activities, making it difficult to differentiate fire-related acoustic signals like crackling or roaring. Additionally, sound waves weaken as they travel through dense vegetation, reducing the detection range and reliability over large areas. Another challenge is balancing sensitivity to avoid false positives (e.g., mistaking animal sounds for fire) and false negatives (failing to detect actual fires). These limitations hinder the standalone effectiveness of sound-based systems in dynamic forest environments

7.1 Future work

Future elevations in sound technology for forest fire administration will probably concentrate on enhancing signal processing algorithms applying machine learning and artificial intelligence. These technologies can enhance the distinction of fire sounds from environmental noise and adjust to different forest ecosystems. Evolving low- cost, energy-effective aural detectors with longer ranges and assimilating them into multi-sensor networks, containing drones, satellites, and IoT systems, will be pivotal for scalability. Furthermore, real- time data emulsion and predictive modeling could fabricate sound technology a critical ingredient of early warning systems, significantly perfecting forest fire spotting and mitigation efforts.

REFERENCES

- [1] M. Grari et al., "Using IoT and ML for Forest Fire Detection, Monitoring, and Prediction: A Literature Review," *J. Theor. Appl. Inf. Technol.*, vol. 100, pp. 5445–5461, 2022.
- [2] M. Yandouzi et al., "Review on forest fires detection and prediction using deep learning and drones," *J. Theor. Appl. Inf. Technol.*, vol. 100, no. 12, pp. 4565–4576, 2022.
- [3] M. Yandouzi et al., "A Lightweight Deep Learning Model for Forest Fires Detection and Monitoring," pp. 697–705, 2023, doi: 10.1007/978-981-19-6223-3_71.
- [4] M. Grari, I. Idrissi, M. Boukabous, O. Moussaoui, M. Azizi, and M. Moussaoui, "Early Wildfire Detection using Machine Learning Model Deployed in the Fog / Edge Layers of IoT," *Indones. J. Electr. Eng. Comput. Sci.*, 2022.
- [5] I. Idrissi, M. Mostafa Azizi, and O. Moussaoui, "A Lightweight Optimized Deep Learning-based Host-Intrusion Detection System Deployed on the Edge for IoT," *Int. J. Comput. Digit. Syst.*, vol. 11, no. 1, pp. 209–216, 2022, doi: 10.12785/ijcds/110117
- [6] "The Sundry: The Physics of Sound." https://www.schoolnet.org.za/PILAfrica/en/web_s/19537/physics3.html (accessed Apr. 26, 2023).
- [7] A. Kherraki and R. El Ouazzani, "Deep convolutional neural networks architecture for an efficient emergency vehicle classification in real-time traffic monitoring," *IAES Int. J. Artif. Intell.*, vol. 11, no. 1, pp. 110–120, Mar. 2022.
- [8] I. Idrissi, M. Azizi, and O. Moussaoui, "Accelerating the update of a DL-based IDS for IoT using deep transfer learning," *Indones. J. Electr. Eng. Comput. Sci.*, vol. 23, no. 2, pp. 1059–1067, Aug. 2021, doi: 10.11591/ijeecs.v23.i2.pp1059-1067.
- [9] M. Boukabous and M. Azizi, "A comparative study of deep learning based language representation learning models," *Indones. J. Electr. Eng. Comput. Sci.*, vol. 22, no. 2, pp. 1032–1040, 2021, doi: 10.11591/ijeecs.v22.i2.pp1032-1040.
- [10] M. Yandouzi et al., "Forest Fires Detection using Deep Transfer Learning," *Int. J. Adv. Comput. Sci. Appl.*, vol. 13, no. 8, pp. 268–275, Oct. 2022, doi: 10.14569/IJACSA.2022.0130832.
- [11] M. Yandouzi et al., "Investigation of Combining Deep Learning Object Recognition with Drones for Forest Fire Detection and Monitoring," *Artic. Int. J. Adv. Comput. Sci. Appl.*, vol. 14, no. 3, p. 2023, 2023, doi: 10.14569/IJACSA.2023.0140342.
- [12] I. Idrissi, M. Boukabous, M. Azizi, O. Moussaoui, and H. El Fadili, "Toward a deep learning-based intrusion detection system for IoT against botnet attacks," *IAES Int. J. Artif. Intell.*, vol. 10, no. 1, pp. 110–120, Mar. 2021, doi: 10.11591/ijai.v10.i1.pp110-120.
- [13] S. D. Correia, J. Fé, S. Tomic, and M. Beko, "Drones as Sound Sensors for Energy-Based Acoustic Tracking on Wildfire Environments," pp. 109–125, Nov. 2021, doi: 10.1007/978-3-030-96466-5_8.
- [14] M. Boukabous and M. Azizi, "Crime prediction using a hybrid sentiment analysis approach based on the bidirectional encoder representations from transformers," *Indones. J. Electr. Eng. Comput. Sci.*, vol. 25, no. 2, Feb. 2022, doi: 10.11591/IJEECS.V25.I2.PP.
- [15] M. Boukabous and M. Azizi, "Multimodal Sentiment Analysis using Audio and Text for Crime Detection," in *2022 2nd International Conference on Innovative Research in Applied Science, Engineering and Technology (IRASET)*, Mar. 2022, pp. 1–5, doi: 10.1109/IRASET52964.2022.9738175.
- [16] I. Idrissi, M. Azizi, and O. Moussaoui, "A Stratified IoT Deep Learning based Intrusion Detection System," in *2022 2nd International Conference on Innovative Research in Applied Science, Engineering and Technology (IRASET)*, Mar. 2022, pp. 1–8, doi: 10.1109/IRASET52964.2022.9738045.
- [17] E. Jeczminek and P. A. Kowalski, "Flattening Layer Pruning in Convolutional Neural Networks," *Symmetry* 2021, Vol. 13, Page 1147, vol. 13, no. 7, p. 1147, Jun. 2021, doi: 10.3390/SYM13071147.
- [18] "machine-learning-articles/how-to-use-sparse categorical-crossentropy-in-keras.md at main · christianversloot/machine-learning-articlesGitHub." <https://github.com/christianversloot/machine-learning-articles/blob/main/how-to-use-sparse-categorical-crossentropy-in-keras.md> (accessed Apr. 26, 2023).
- [19] D. Ali, M. M. S. Missen, and M. Husnain, "Multiclass Event Classification from Text," *Sci. Program.*, vol. 2021, 2021, doi: 10.1155/2021/6660651.
- [20] Y. Hammoudi, I. Idrissi, M. Boukabous, Y. Zerguit, and H. Bouali, "Review on maintenance of photovoltaic systems based on deep learning and internet of things," *Indones. J. Electr. Eng. Comput. Sci.*, vol. 26, no. 2, May 2022.
- [21] Mounir Grari, Mohammed Boukabous, Mimoun Yandouzi, Mohammed Berrahal, Idriss Idrissi, Omar Moussaoui, Mostafa Azizi, Mimoun Moussaoui "Forest Fire Detection And Monitoring Through Environment Sound Spectrum Using Deep Learning" *Journal of Theoretical and Applied Information Technology* 15th October 2023. Vol.101. No 19